




Water Tight Technologies, LLC
3815 River Crossing Parkway, Ste 100
Indianapolis, IN 46240



SECTION 1 – PRODUCT IDENTIFICATION

Product Name: Uncured EPDM Flashing with Tape	24 Hour Emergency Telephone Number: 800-424-9300 CHEMTREC
Chemical Name/Synonyms: 6, and 12 inch Uncured Flashing	Manufacturer's Name: Water Tight Technologies, LLC
Chemical Family: Mixture	Manufacturer's Address: 3815 River Crossing Parkway, Ste 100 Indianapolis, IN 46240
Chemical Formula: Not Established	NFPA Acute Hazard Rating: Health 1, Flammability 1, Reactivity 0 HMIS Acute Hazard Rating: Health 0, Flammability 1, Reactivity 0

SECTION 2 – CHEMICAL COMPOSITION

Chemical Name:	Common Name:	CAS#:	% (by wt)	Exposure Limits:
Nonhazardous as per 29 CFR 1910.1200.	None	None	100	None Established


SECTION 3 – PHYSICAL & CHEMICAL CHARACTERISTICS

Appearance/Odor: Black, solid with no odor	Physical State: Solid	Solubility in Water: None
Boiling Point: NA	Specific Gravity (HO=1) 1.10	Melting Point: Not Established
Vapor Pressure: NA	Vapor Density (Air=1) Not Established	Freezing Point: Not Established
Percent Volatiles: 0.7 % maximum	Evaporation Rate: NA	Reactivity in Water: Not Established
pH (Full Strength) Not Established	pH (Recommended Dilution): Not Established	Refraction Index: NA

Uncured EPDM Flashing with Tape 1/4
 March 21, 2007



Water Tight Technologies, LLC
3815 River Crossing Parkway, Ste 100
Indianapolis, IN 46240



SECTION 4- FIRE & EXPLOSION HAZARD DATA

Flash Point: > 200° C	Flammable Limits (in air): NA
Extinguishing Media: Dry chemical, carbon dioxide, water fog or foam. Water should be used to keep fire exposed containers cool.	Fire Fighting Procedures: Treat as Class "B" Fire. Use water spray to cool adjacent surfaces and fire exposed containers. Protect against inhalation of combustion products. Firefighters should wear full protective clothing including self-contained breathing apparatus to prevent inhalation of smoke and decomposition products. Toxic fumes and vapors may be involved.
Hazardous Decomposition Products: May form toxic materials: Carbon Dioxide, Carbon Monoxide, Oxide of nitrogen, Sulfur Dioxide, and acrid smoke and irritating fumes.	Special Fire & Explosion Hazards: None Known
Method Used Not Established	Auto-Ignition Temperature: Not Established


SECTION- 5 HEALTH HAZARD DATA

Permissible Exposure Limit: Not Established	Signs and Symptoms of Exposure: Treat as a foreign object in eye. Eye contact may cause severe eye irritation, redness, tearing and blurred vision. Flush with large amounts of water. Get medical attention if irritation of eyes or skin persists.
Effects of Overexposure: Not Established	
Acute: Due to physical nature of this product, eye contact, ingestion and inhalation are unlikely.	Chemical Listed as a Carcinogen (or Potential Carcinogen): National Toxicology Program: NO L.A.R.C. Monographs: NO OSHA: NO
Chronic: No known adverse effects.	

Uncured EPDM Flashing with Tape 2/4
 March 21, 2007



Water Tight Technologies, LLC
3815 River Crossing Parkway, Ste 100
Indianapolis, IN 46240



Emergency & First Aid Procedures:

Eye Contact:

Contact with eyes may result in tearing, irritation, redness and swelling. Hold eyes open and flush immediately with a gentle stream of water for at least 15 minutes, preferable at an eyewash fountain.

Skin Contact:

Thoroughly wash affected area with soap and water.

Inhalation:

Due to the physical nature of this product, inhalation is unlikely.

Ingestion:

Due to the physical nature of this product, ingestion is unlikely.

Primary Route of Entry:

Skin contact.

SECTION 6 – REACTIVITY DATA

Stability:

Stable

Incompatibility:

Strong oxidizers, acids, bases.

Hazardous Decomposition Products:

Carbon dioxide and carbon monoxide, oxides of nitrogen, sulfur dioxide, and partially burned carbon.

Hazardous Polymerization:

NA

Conditions to Avoid:

Open flames, sparks, and closed areas that restrict adequate ventilation. Exposure to temperatures in excess of 130° F

SECTION 7 - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled:

Small spill:

Shovel or scoop into a sealable container for disposal.

Large Spill:

Same as small spill.

Waste Disposal Method:

Dispose in a landfill in accordance with local, state and federal regulations.

SECTION 8 – SPECIAL PROTECTION

Respiratory Protection:

Not required under normal conditions of use.

Eye Protection:

Impervious safety glasses recommended.

Protective Gloves:

Not required under normal conditions of use.

Other Protective Equipment:

Under normal application conditions, protective glasses, gloves, and clothing are adequate.


Ventilation:

Provide adequate ventilation to maintain airborne concentrations below OSHA PELs.

Uncured EPDM Flashing with Tape 3/4
March 21,2007



Water Tight Technologies, LLC
3815 River Crossing Parkway, Ste 100
Indianapolis, IN 46240



SECTION 9 – SPECIAL PRECAUTIONS OR OTHER COMMENTS

Storage/Handling:

Store in cool, dry, well ventilated facility. Do not store or handle at temperatures in excess of 130° F. Store and use away from all sources of sparks, direct heat and ignition.

Other Precautions:

Provide adequate ventilation and avoid prolonged or repeated contact with the skin. Wash with soap and water after contact.

Work/Hygienic Practices:

Maintain good personal hygiene practices. Wash contaminated clothing before reuse. Do not eat, drink, or smoke in work areas. Wash exposed skin before eating, drinking, smoking, or applying cosmetics.

SECTION 10 – TRANSPORTATION

Regulatory Agency:

Not Regulated

Identification Number:

Not Applicable

Proper Shipping Name:

Not Applicable

Labels Required:

Not Applicable

Hazard Classification:

Not Applicable

Other Requirements:

Not Applicable

SECTION 11 – MISCELLANEOUS INFORMATION

Additional Comments:

This product is considered to be a finished article as per 29 CFR 1910.1200 © and is therefore exempt from the requirements of the Hazard Communication standard.

Date of Previous MSDS:

September 26, 1990

Changes Since Previous MSDS:

**Comment change in sections: 1 thru 9
Add sections: 10,11**

Telephone Number for Additional Information:

(574) 293-9096

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information is accurate, complete, or representative. Water Tight Technologies, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons if reasonable safety procedures are not followed.